

Description

ADJUSTING APPARATUS

BACKGROUND OF INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to an adjusting apparatus, and more particularly to an adjusting apparatus for use in angle or linear adjustment.

[0003] 2. Description of the Prior Art

[0004] Referring to FIG. 1, a rear-projection television of the prior comprises a cover 1 and an optical projection system placed inside the cover 1. The optical projection system comprises an optical engine 2, a small reflection mirror 3, a big reflection mirror 4, and a screen 5. An image beam provided by the optical engine 2 impinges onto the small reflection mirror 3 on the front of the optical engine 2, and then onto the big reflection mirror 4 placed on the light path of the reflection beam of the small reflection mirror 3. Finally, the image beam reflected by the big reflection mirror 4 projects on the screen 5 to display an

image.

[0005] The optical engine 2 provides the image beam whose light path determines if the image of the screen is distortion. Hence, each optical device of the optical projection system, e.g. optical engine 2, small reflection mirror 3, and big reflection mirror 4, must be positioned at relatively exact positions and projection angles. But the optical devices inherently have manufacturing tolerances and assembly tolerances. Therefore, after assembling, the optical projection system need to adjust the relative positions and inclined angles of optical devices by use of an adjusting apparatus. Then, the optical projection system is able to reach predetermined shrunk and amplified ratio and resolve the image distortion and un-focus for achieving the optimum performance.

[0006] Referring to FIG. 2, a prior art adjusting apparatus 10 for an optical engine comprises a base 11, a bolt 12, and two sliding plates 13, 14 and a rotating carrier 15 sequentially placed on the base 11. The optical engine (not shown) is placed on the rotating carrier 15, and the highness of optical engine can be adjusted by rotating the bolt 12. Two pairs of guide rails 131, 141 are respectively placed along the corresponding sides of the two sliding plates 13, 14,

to limit to the forward or backward, and right or left movement. One end of a rotating shaft pivots on the center of the rotating carrier 15, and the other end is fixed to the sliding plate 14. By rotating the rotating shaft, the sliding plate 14 rotates along the center of the rotating carrier 15 to adjust horizontal angle. With the above-mentioned adjusting apparatus, the optical engine can adjust highness, forward, backward, right and left directions, as well as horizontal angle for the optical engine. The above-mentioned adjusting apparatus can only provide the horizontal angle adjustment for optical engine, but not provide angle adjustments of left and right inclinations so that it cant effectively resolve the problems of image distortions and un-focus on screen. Hence, the adjusting apparatus for the optical engine needs to be improved.

SUMMARY OF INVENTION

[0007] One object of the present invention is to provide an adjusting apparatus, which modifies the rotation angle of projection images and the light path of image beam by adjusting left and right angles of inclination of an optical engine to resolve distortion of projection images and un-focus on a screen and to improve projection performance.

- [0008] Another object of the present invention is to provide an adjusting apparatus with multi-axis adjustment to simplify the assembly for a rear-projection TV.
- [0009] Further object of the present invention is to provide an adjusting apparatus, which can form a module of an optical engine and a small reflection mirror.
- [0010] To achieve the above and other objects, an adjusting apparatus of the present invention comprises a base, a supporting frame, a fixed plate, a sliding stand, and a carrier carrying an optical engine. The supporting frame, the fixed plate, the sliding stand, and the carrier sequentially stack on the base. The side surfaces of the supporting frame form at least one flank. The flank has at least one sliding slot. The base has at least one bulge that cooperates with the sliding slot. A third adjusting device has one end clipping to the base and the other end screwing to and driving the supporting frame moving. A third fixing device screws together the supporting frame and the base. The fixed plate has at least one sliding bulge. The side surface of the sliding stand has at least one flank. The flank has a sliding slot corresponding to the bulge. A first adjusting device has one end clipping to the fixed plate, the other end screwing to and driving the sliding

stand axis moving. A first fixing device screws and connects to the sliding stand and the fixed plate. The sliding stand and the carrier respectively have corresponding arc surface. The center of the sliding stand has an opening, and the carrier has a block corresponding to the opening. A second adjusting device passes through the sliding stand and has one end clipping to the block to push the carrier rotating and change inclination angle of the optical engine. A second fixing device screws and connects to the carrier and the sliding stand.

BRIEF DESCRIPTION OF DRAWINGS

- [0011] The above and other objects, advantages, and features of the present invention will be understood from the following detailed description of the invention when considered in connection with the accompanying drawings below.
- [0012] FIG. 1 is a schematic view of an optical projection for rear-projection TV of the prior art.
- [0013] FIG. 2 is a perspective view of an adjusting apparatus of optical engine of the prior art.
- [0014] FIG. 3 is a perspective view of an adjusting apparatus of the first embodiment of the present invention.
- [0015] FIG. 4 is an exploded perspective view of an adjusting apparatus of the first embodiment of the present invention.

- [0016] FIG. 5 is a sectional view of an axis adjustment of an adjusting apparatus of the present invention.
- [0017] FIG. 6 is a front view of an angle adjustment of an adjusting apparatus of the present invention.
- [0018] FIG. 7 is a perspective view of a reflection mirror combined with an adjusting apparatus of the present invention.
- [0019] FIG. 8 is a perspective view of an adjusting apparatus of the second embodiment of the present invention.
- [0020] FIG. 9 is an exploded perspective view of an adjusting apparatus of the second embodiment of the present invention.

DETAILED DESCRIPTION

- [0021] The First Embodiment
- [0022] Referring to FIG. 3 and FIG. 4, an adjusting apparatus 20 of the present invention comprises a base 21, a supporting frame 22, a fixed plate 23, a sliding stand 24, and a carrier 25. The upper surface 251 of the carrier 25 has at least one fixing pin 252 for fixing an optical engine (not shown).
- [0023] The base 21 has an upper surface 211. Two edges of the upper surface 211 have a plurality of bulges 212 and fix-

ing openings 213, and one of the edges further has a hold 214. Inside the hold 214 has a receiver 2141. A third adjusting device 215 passes through the hold 214 and has one end clipping into the receiver 2141 of the hold 214.

[0024] The supporting frame 22 is placed on the upper surface 211 of the base 21, and has a top surface 221 which exists an angle of inclination to the base 21. Two edges of the top surface 221 respectively form a left flank 222 and a right flank 223, which form a hat-shape body. The left flank 222 and the right flank 223 have a plurality of sliding slots 224A and 224B. The sliding slots 224A correspond to the bulges 212. A plurality of third fixing devices 225 is provided to perpendicularly pass through the sliding slots 224B and, then, screw to the fixing openings 213 to connect the base 21 and the supporting frame 22. The supporting frame 22 has an adjusting opening 226 behind the backside of the hold 214. One end of the third adjusting devices 215 parallel to the direction of sliding slots 224A passes through the hold 214 and, then, screws to the adjusting opening 226 to drive the movement of the supporting frame 22.

[0025] Referring to FIG. 5 showing function of the adjusting apparatus 20, a supporting point is formed by using the re-

ceiver 2141 of the hold 214 to clip one end of the third adjusting device 215, and the bulges 212 guides the sliding slot 224B. As loosening the third fixing device 225, the third adjusting device 215 is rotated to drive the supporting frame 22 moving along the direction of the sliding slot 224A to the predetermined position, and then the third fixing device 225 is fastened to fix the supporting frame 22. On the contrast, as loosening the third fixing device 225, the third adjusting device 215 is reversely rotated to drive the supporting frame 22 to the predetermined position in opposite direction. Therefore, the adjusting apparatus 20 of the present invention can reach the first axis adjustment.

[0026] Referring to FIG. 3 and FIG. 4 again, the fixed plate 23 is screwed with a screwing device 231 to the top surface 221 of the supporting frame 22. Due to the inclination top surface 221, there is an angle of inclination between the fixed plate 23 and the base 21. The fixed plate 23 has an upper surface 232, on which has a plurality of bulges 233 and fixing openings 234, and one edge of the fixed plate 23 has a hold 235. A receiver 2351 is inside the hold 235, and a first adjusting device 236 passes through the hold 235 and has one end clipping into the receiver 2351

of the hold 235.

[0027] The sliding stand 24 is placed on the upper surface 232 of the fixed plate 23, whose two edges form a left flank 241 and a right flank 242. The left flank 241 and the right flank 242 have a plurality of sliding cavities 243A corresponding to the bulges 233 and a plurality of sliding cavities 243B. First fixing devices 244 perpendicularly pass through the sliding cavities 243B. The side surface of the sliding stand 24 has a screw hole 245 behind the backside of the hold 235 of the fixed plate 23. One end of the first adjusting devices 236 parallel to the direction of sliding cavities 243A passes through the fixed plate 23 and, then, screws to the screw hole 245 to drive the sliding stand 24 moving along the direction of the sliding cavities 243A.

[0028] Referring to FIG. 5 which shows function of the adjusting apparatus 20, as loosening the first fixing device 244, the bulges 233 and the sliding cavities 243 cooperate with each other to guide and, the receiver 2351 of the hold 235 clips one end of the first adjusting device 236 to form a supporting point. So press the first adjusting device 236 to drive the sliding stand 24 moving along the direction of the sliding cavity 243A to the predetermined position. Then, the first fixing device 244 screws to fix the sliding

stand 34. On the contrast, as loosening the first fixing device 244, the first adjusting device 236 is reversely rotated to drive the sliding stand 24 to the predetermined position in opposite direction. Therefore, the above-mentioned adjusting apparatus 20 can reach the second axis adjustment.

[0029] As shown in FIG. 3 and FIG. 4, the center of the sliding stand 24 has a frame 248. The frame 248 has a rectangular opening 247 at the center of its upper arc surface 246. Two edges of the frame 248 have a screwing hole 249 interlinked to the opening 247. A second adjusting device 253 passes through the screwing hole 249. End surfaces of the frame 248 have fixing openings 2481.

[0030] The carrier 25 is placed on the arc surface 246 of the sliding stand 24. Down surface 254 of the carrier 25 is a convex arc surface corresponding to concave arc surface of the sliding stand 24. Two end surfaces of the carrier 25 respectively fasten an arc plank 256. The arc planks 256 have arc cavities 2561 according to the arc curvature of the sliding stand 24. The positions of the arc cavities 2561 are corresponding to the fixing opening 2481 of the sliding stand 24. A second fixing device 257 passes through the arc cavities 2561 and screws to the fixing

opening 2481 to fix the carrier 25. Inside surface of the arc plank 256 has a plurality of supporting pins 2562 which clip the upper arc surface 246 of the frame 248 so that the carrier 25 and sliding stand 24 form sliding connection. Down surface has a block 255 corresponding to the position of the opening 247. The block 255 is smaller than the rectangular opening 247 and is received inside the opening 247 so that the second adjusting device 253 passes through the screwing hole 249 and, then, one end of the second adjusting device 253 is clipped to the block 255.

[0031] Referring to FIG. 6 which shows function of the adjusting apparatus 20, as loosening the second fixing device 257, the second adjusting device 253 is rotated to push the block 255 so that the carrier 25 rotating along the arc surface of the sliding stand 24 to adjust the left and right angles of inclination of the carrier 25. On the contrast, the second adjusting device 253 is reversely rotated to drive the carrier 25 to the predetermined position. Therefore, the above-mentioned adjusting apparatus 20 can reach the third axis adjustment. In addition, as the center of optical engine is placed the center of the arc surface of the sliding stand 24, the second adjusting device 253 makes

optical engine rotate around the center of optical axis so that it can adjust the rotation angle of projection images and can improve distortion of projection images and unfocus on screen.

[0032] Hence, as optical engine fastens on the upper surface 251 of the carrier 25, by respectively rotating the first adjusting device 236, the second adjusting device 253 and the third adjusting device 215, the position and inclination angle of optical engine are quickly adjusted to make image beam, provided by optical engine, precisely project on screen and reach optimum performance.

[0033] In addition, there is an inclination angle between the supporting frame 22 and base 21. The fixed plate 23, the sliding stand 24 and carrier 25 having optical engine sequentially stack on the supporting frame 22 so that there is an angle of inclination between optical engine and the base 21. Hence, the adjusting apparatus 20 can apply to optical system of rear-projection TV whose optical engine needs inclined projecting beam (shown in FIG. 1). As a result, the third adjusting device 215 moves optical engine along the axis of the base 21, the first adjusting device 236 makes optical engine move along the inclined surface of the supporting frame 22, and the second adjusting de-

vice 253 makes optical engine rotate around the center of the arc surface to adjust the left and right inclination angle of optical engine.

[0034] Furthermore, referring to FIG. 7, two edges of the top surface 221 of the supporting frame 22 respectively have a connection plank 227 for screwing a small mirror 3 so that the small mirror 3 and optical engine can combine as a module to place inside rear-projection TV to simplify the fabricating steps.

[0035] The Second Embodiment

[0036] As shown in FIG. 8 and FIG. 9 that show an adjusting apparatus 30 of the second embodiment of the present invention, the basic structure of the present embodiment is similar to that of the first embodiment. The differences between the present embodiment and the first embodiment are that a top surface 321 of a supporting frame 32 is parallel to a upper surface 311 of a base 31 such that a fixed plate 33, a sliding stand 34, and a carrier 35 having optical engine, sequentially stacking on the supporting frame 32, are still parallel to the base 31. The basic method for adjusting position of optical engine of the present embodiment is the same as the first embodiment. By rotating the first adjusting device 336, the second ad-

justing device 353, and the third adjusting device 315, the position and inclination angle of optical engine can be quickly adjusted to make image beam, provided by optical engine, precisely project on screen and reach optimum performance.

[0037] It will be apparent to those skilled in the art that in light of the forgoing disclosure, many alternations and modifications are possible in the practice of this invention without departing from the spirit or scoop thereof. Accordingly, the scoop of the invention is to be considered in accordance with the substance defined in the following claims.